

EPCDESIGNTOOL_MD-EM Mechanical Die for Electromigration Testing

EPCDESIGNTOOL_MD-EM are sized equivalent to EPC device EPC2016C with die size 2.1 mm x 1.6 mm.

These devices have internal metal layers shorted for electromigration reliability testing.

Figure 1: Die Photo for EPCDESIGNTOOL_MD-EM





Figure 2: Die Outline (Solder Bar View)



DIM	MICROMETERS		
	MIN	Nominal	MAX
Α	2076	2106	2136
В	1602	1632	1662
C	1379	1382	1385
d	577	580	583
e	235	250	265
f	195	200	205
g	400	400	400

Pad 1 is Gate;


Pads 3, 5 are Drain

Pads 4, 6 are Source

Pad 2 is Substrate

NOTE: Drain and Source are internally shorted at Metal 1 to create a metal resistor

Figure 3: Side View





EPCDESIGNTOOL_MD-EM


Mechanical Die for Electromigration Testing


Figure 4: Recommended Land Pattern (units in µm)

Land pattern is solder mask defined. Solder mask opening is 180 $\mu\text{m}.$

Recommended stencil should be 4mil (100 µm) thick, must be laser cut,

Stencil opening can be per the bump drawing.





Pad 1 is Gate;

Pads 3, 5 are Drain

Pads 4, 6 are Source

Pad 2 is Substrate

Additional assembly resources available at epc-co.com/epc/DesignSupport/AssemblyBasics.aspx

Efficient Power Conversion Corporation (EPC) reserves the right to make changes without further notice to any products herein. EPC does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of other.

 ${\sf eGaN}^* \ is \ a \ registered \ trademark \ of \ Efficient \ Power \ Conversion \ Corporation.$

EPC Patent Listing: epc-co.com/epc/AboutEPC/Patents.aspx